



Trade name: Avantama P-10

Safety data sheet

1 Identification of the substance/mixture and of the company

1.1 Product identifiers

Trade name: <u>Avantama P-10</u> Product number: 6040

REACH No.: A registration number is not available for this substance as the substance or its uses are exempted from

registration, the annual tonnage does not require a registration or the registration is envisaged for a later

registration deadline.

1.2 Relevant identified uses of the substance or mixture

Identified uses: Laboratory chemicals, Manufacture of thin films

1.3 Details of the supplier of the safety data sheet

Distributing company:

Avantama AG

Laubisruetistrasse 50

8712 Staefa Switzerland

Tel.-Nr.: +41 44 244 51 00

Informational: info@avantama.com

1.4 Emergency telephone number:

Schweizerisches Toxikologisches Informationszentrum (STIZ), Switzerland

Tel.-Nr.: +41 (0)44 251 5151

2 Hazards identification

2.1 Classification of the substance or mixture

For the full text of the H-statements and P-phrases mentioned in this section, see Section 16

Classification according to Regulation (EC) No 1272/2008 [EU-GHS/CLP

Flammable liquids (cat. 2)	H225
Acute toxicity (cat. 4)	H302
Eye irritation (cat. 2)	H319
Specific target organ toxicity – single exposure (cat. 3)	H336

Classification systems:

The classification corresponds to the current EC-Lists and is complemented with literature and the company knowledge.

2.2 Label elements

Labeling according to Regulation (EC) Nr. 1272/2008

The product is classified and labeled according to the CLP regulation.

Pictogram





Signal word: Danger Hazard statement(s)

H225 Highly flammable liquid and vapor

H302 Harmful if swallowed

H319 Causes serious eye irritation

H336 May cause drowsiness and dizziness



Version 6 Revised: 15th June 2024

According to (EC) Nr. 453/2010

Trade name: Avantama P-10

Precautionary statement(s)

P210 Keep away from heat/ sparks/ open flames/ hot surfaces. – No smoking.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P280 Wear protective gloves protective clothing eye protection face protection P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or physician

2.3 Supplemental Hazard

The applied nanoparticles may be enriched in human body and/ or in organisms.

3 Composition / information on ingredients

Chemical characterization: Mixtures

Description: Mixture made of the following ingredients including non-hazardous admixtures.

Hazardous ingredient	s:	
CAS: 67-63-0	Isopropanol	90-100%
EC: 200-661-7	Flam. Liq. 2; H225; Eye Irrit. 2; STOT SE 3; H319; H336	
CAS: 1314-35-8	Tungsten(VI) oxide	< 10%
EC: 215-231-4	Acute Tox. 4; H302	

Additional indication:

Comprised tungsten oxide is present as nanoparticles.

For the full text of the H-statements and P-phrases mentioned in this section, see Section 16

4 First aid measures

4.1 Description of first aid measures

If inhaled: If breathed in, move person into fresh air. If not breathing, give artificial respiration.

Consult a physician.

In case of skin contact: Wash off with soar and plenty of water.

In case of eye contact: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

By Swallowed: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse

mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labeling (see section 2.2) and/or in section 11.

4.3 Indication of any immediate medical attention and special treatment needed.

No data available.

5 Firefighting measures

5.1 Extinguishing media

Unsuitable media:

Water jet

Suitable media:

CO₂, alcohol-resistant foam, dry chemical

5.2 Special hazards arising from the substance or mixtures

Tungsten/Tungsten oxide, Carbon oxide

5.3 Advice for firefighters

Specific protective equipment: Wear self-contained breathing apparatus for firefighting if necessary. Further information: Use water spray to cool unopened containers. Prevent fire-extinguishing water from contaminating surface water or the ground water system.



Trade name: Avantama P-10

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Pick up and arrange disposal with liquid binding material (chemical binders, sand, diatomite, acid binders, universal binders, sawdust). Then collect by wet-brushing and place in container for disposal according to local regulations. Provide adequate ventilation.

6.4 Reference to other sections

For handling see section 7

For disposal see section 13

7 Handling and storage

7.1 Handling

Precaution for safe handling

Ensure adequate ventilation. Use personal protective equipment. Avoid breathing vapors, mist or gas. Avoid contact with skin and eyes. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. Usual measures of the preventing fire protection.

Avoid formation of aerosols, do not inhale.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Containers, which are opened, must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1 no other specific uses are stipulated.

8 Exposure controls/personal protections

Additional indication for technical installation: No data available, see section 7.

8.1 Control parameters

Components requiring monitoring of workplace exposure limit values:		
2-Propanol (90-100%		
MAK (Switzerland,	200 mL/m³	
(max. workplace concentration)	500 mg/m ³	
Tungsten(VI) oxide (<	10%)	
MAK (Switzerland,	5 mg/m³	
(max. workplace concentration)	Inert dust, general dust limit value; inert dust is termed by the current state of scientific knowledge as dust which is not resorbed, no increased formation of connective tissue in lungs (fibrogenic effect) is observed and no specific symptoms of illness are triggered. Such kind of dust may infringe the functionality of the respiratory system by mechanical irritation. Therefore a MAK of 3 mg/m³ of alveolar dust is applied, measured according to EN 481 and also 10 mg/m³ for respirable dust. The here used tungsten oxide is not existent in form of dust, but can be inhaled in form as an aerosol.	



Trade name: Avantama P-10

8.2 Exposure controls

Personal protective equipment

General protective and hygienic measures

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of the day. Keep away from food, beverage and feeding stuff.

Take off contaminated clothing immediately.

Eye/face protection



Safety glasses with side-shields conforming to EN166. Use equipment for eye protection tested and approved under appropriate government standards.

Respiratory protection

For mist /aerosol exposures use respiratory protection.

Recommended filter type: ABEK P3

Skin protection



Handle with gloves. Use proper glove removal technique to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Glove material

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Recommended material: Nitrile rubber

Full contact:

Minimum layer thickness: 0.4 mm Break through time: 480 min

Splash contact

Minimum layer thickness: 0.4 mm Break through time: 60min

Body protection

Type of protective equipment according to risk evaluation.

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

9 Physical und chemical properties

9.1 Information on basic physical and chemical properties		
General properties		
Appearance:		
Form:	Liquid	
Color:	Blueish, translucent	
Odor:	Alcohol-like	
Odor threshold:	No data available	
pH:	No data available	
Phase transition		
Melting point/melting range:	No data available	
Initial boiling point/boiling range:	No data available	
Flash point:	No data available	
Flammability (solid, gas):	No data available	
Ignition temperature:	No data available	
Decomposition temperature:	No data available	



Trade name: Avantama P-10

Auto-ignition temperature:	No data available
Explosive properties:	No data available
Explosion limit:	
Lower:	No data available
Upper:	No data available
Oxidizing properties	No data available
Vapor pressure at 20°C:	No data available
Density at 20°C	No data available
Relative density	No data available
Vapor density	No data available
Evaporation rate	No data available
Solubility in / Miscibility with Water:	
	Miscible but not stable
Partition coefficient:	No data available
Viscosity:	
Dynamic:	2-3 mPa s at 23°C
Kinematic:	No data available
Solvent content:	
Organic solvents:	90-100%
VOC (EU):	90-100%
VOCV (CH):	90-100%
Solid load:	<10%
9.2 Additional safety information:	Primary particle size (dried appearance): 5-50 nm
	Particle size (agglomerate size) in
	Dispersion: <100 nm
	Zeta-Potential of nanoparticles is unknown.
	Nanoparticle solubility: poorly soluble (0.1 g/L)

10 Stability and Reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions

10.3 Thermic decomposition / conditions to avoid:

No decomposition under recommended application.

10.4 Possibility of hazardous reactions

No data available.

10.5 Conditions to avoid

Heat, flames and sparks. Extreme temperatures and direct sunlight

10.6 Incompatible materials

Strong bases, strong oxidizing agents, strong acids, halogenated compounds.

10.7 Hazardous decomposition products

Other decomposition products – no data available.

In the event of fire: See section 5



Trade name: Avantama P-10

11 Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Classification	-relevant LD/	LC50 values:
2-Propanol		
Oral	LD50	4'045 mg/kg (rat); Remarks: Behavioral: Altered sleep time and somnolence
Inhalation	LC50	16'000 ppm (rat – 8h)
Dermal	LD50	12'800 mg/kg (rabbit)
Tungsten(VI)	oxide	
Oral	LD50	1'059 mg/kg (rat); Remarks: Behavioral: Drowsiness, excitement and myasthenia

Primary corrosion/irritation:

Respiratory: May be harmful, may cause irritation of respiratory system by inhalation of aerosol or dust.

Skin (rabbit): Mild skin irritation
Eye (rabbit): Eye irritation – 24h
Sensitizations: No data available

Carcinogenicity: This product is or contains a component that is not classifiable as to its carcinogenicity based on

its IARC, ACGIH, NTP, or EPA classification

IARC: 3 – Group 3: Not classifiable as to its carcinogenicity to humans (2-Propanol)

Additional toxicological information:

RTECS: NT8050000

2-Propanol: Central nervous system depression, prolonged or repeated exposure can cause: Nausea, headache, vomiting, narcosis, drowsiness, and overexposure may cause mild, reversible liver effects. Kidney – Irregularities – Based on human evidence.

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

12 Ecological information

12.1 Toxicity

Aquatic Toxicity:

Isopropanol: LC50: 9'640 mg/L – 96h (Pimephales promelas)

EC50: 5'102 mg/L – 24h (Daphnia magna)

Immobilization EC50: 6'851 mg/L – 24h (Daphnia magna) EC50: ≥ 2'000 mg/L -72h (Desmodesmus subspicatus)

EC50: ≥ 1'000 mg/L -24h (Algae)

Tungsten oxide: No data available

12.2 Persistence and degradability

2-Propanol: Biodegradability: 95% - 21d

Tungsten(VI) oxide: No data available

12.3 Behavior in environmental compartments:

Bio-accumulative potential: No data available.

Mobility in soil: No data available.

12.4 Additional ecological indication:

General indication: Do not let product enter drains, surface water or the ground water system. Discharge into the environment must be avoided.

12.5 Results of PBT- and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted.

12.6 Other adverse effects

Very toxic to aquatic life.





Trade name: Avantama P-10

13 Disposal considerations

13.1 Waste treatment methods

Recommendation: Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting, as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company.

13.2 Contaminated packaging

Recommendation: Dispose of as unused product

Recommended detergent: Ethanol

14 Transport information

Land transport ADR/RID and GGVSEB (cross-border/interior):



ADR/RID-GGVSEB class: 3 flammable liquid

UN number:1219Packing group:IIHazard label:3

UN proper shipping name: Isopropanol Tunnel restriction code D/E

Transport hazard class(es) 3

Sea shipment IMDG/GGVSee



IMDG/GGVSee class: 3 flammable liquid

UN number:1219Hazard label:3Packing group:IIEMS code:F-E, S-DMarine pollutant:NoUN proper shipping name:Isopropanol

Air transport ICAO-TI und IATA-DGR



ICAO/IATA class: 3
UN/ID number: 1219
Hazard label: 3
Packing group: II

UN proper shipping name: Isopropanol

15 Regulatory information

Chemical Safety Assessment: For this product a chemical safety assessment was not carried out





Trade name: Avantama P-10

16 Other information

The above information is believed to be correct but does not purport to be all-inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Avantama Ltd shall not be held liable for any damage resulting from handling or from contact with the above product.

This safety data sheet contains nano-specific information.

16.1 H-statements

H225 Highly flammable liquid and vapor

H302 Harmful if swallowed

H319 Causes serious eye irritation

H336 May cause drowsiness and dizziness

16.2 Precautionary statement(s)

P210 Keep away from heat/ sparks/ open flames/ hot surfaces. – No smoking.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P280 Wear protective gloves protective clothing eye protection face protection P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or physician

16.3 Abbreviation and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

IARC: International agency for research of cancer ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labeling of Chemicals

VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

EC50: half maximal effective concentration

Eye irrit.: Eye irritation Flam. Liq.: Flammable liquids

STOT SE: Specific target organ toxicity – single exposure